



2019 SNOWTHROWERS



COMPACT IN SIZE IMPRESSIVE IN PERFORMANCE



**SMALL
DRIVEWAY**



**UP TO 30'
THROWING¹**



**LIGHT TO
MODERATE
SNOWFALL**

SINGLE-STAGE

The single-stage line-up was born after countless hours of consumer research to discover the important features you were looking for, like a Briggs & Stratton Snow Series™ engine for easy starting, and premium features to help get the job done quickly, such as electric chute rotation, headlights and the SnowShredder™ Serrated Auger.

22 inch clearing width
9.50 ft-lbs gross torque²

Briggs & Stratton 950 Snow Series™ OHV Engine, 208cc
1022 (Recoil Start)

22 inch clearing width
9.50 ft-lbs gross torque²

Briggs & Stratton 950 Snow Series™ OHV Engine, 208cc
Electric Start
1022E

22 inch clearing width
9.50 ft-lbs gross torque²

Briggs & Stratton 950 Snow Series™ OHV Engine, 208cc
Remote Chute Rotation
1022ER

22 inch clearing width
9.50 ft-lbs gross torque²

Briggs & Stratton 950 Snow Series™ OHV Engine, 208cc
SnowShredder™ Serrated Auger
1022EE

22 inch clearing width
11.50 ft-lbs gross torque²

Briggs & Stratton 1150 Snow Series™ OHV Engine, 250cc
SnowShredder™ Serrated Auger
1222EE



EASY CLEANING

The auger-assisted drive system makes contact with the ground, helping you move the snowthrower forward with little effort.



EASY CONTROL

Quick-adjust deflector with easy-to-use options such as remote chute rotation and electric chute rotation.



SNOWSHREDDER™ SERRATED AUGER

Multiple individual serrated surfaces provide advanced ice chopping and snow clearing power.

ADDITIONAL FEATURES:

Wear-resistant auger, integrated headlight (1022EE & 1222EE only) and 3-Year limited warranty.³

 **TEXT 'SNOW' TO 33988**
TO SEE THEM IN ACTION
DATA RATES APPLY.

SELECT DUAL-STAGE

The SELECT dual-stage snowthrowers have the features and power of larger snowthrowers with the maneuverability of smaller machines, all at an attractive price. Built to handle even the toughest winters, they include heavy-duty welded construction and components. Powered by a durable and reliable Briggs & Stratton® engine and you've got one impressive machine.



EASY MANEUVERABILITY

Dual-trigger steering controls make turning easy, allowing you to stop the power to either wheel, turning the machine left or right.

FREE HAND™ CONTROL

Free Hand™ Control allows you to drive with one hand while changing speed or the deflector direction with the other hand.

STEEL DASH WITH INTEGRATED LED HEADLIGHTS

The heavy-duty steel dash panel includes convenient dash-mounted chute rotation and deflector controls.

24 inch clearing width
9.50 ft-lbs gross torque²

Briggs & Stratton
950 Snow Series™ OHV
Engine, 208cc
1024

27 inch clearing width
11.50 ft-lbs gross torque²

Briggs & Stratton
1150 Snow Series™ OHV
Engine, 250cc
1227

30 inch clearing width
14.50 ft-lbs gross torque²

Briggs & Stratton
1450 Snow Series™ OHV
Engine, 306cc
1530

 TEXT 'SELECT' TO 33988
TO SEE THEM IN ACTION
DATA RATES APPLY.

ADDITIONAL FEATURES: Electric start, durable friction disk with dual trigger steerable transmission, heated hand grips, aluminum gear case, LED headlights and 3-Year limited warranty.³

¹Capacity and throwing distances can be affected greatly by conditions.

²All power levels are stated gross torque at 2600 RPM per SAE J1940 as rated by Briggs & Stratton.

³See operator's manual or www.simplicitymfg.com for complete warranty details.



**MEDIUM-
LARGE
DRIVEWAY**



**UP TO 40'
THROWING¹**



**MODERATE
SNOWFALL**

BALANCE
CONVENIENCE
AND
PERFORMANCE



POWERFUL PERFORMANCE FOR TOUGH JOBS



**5 YEAR LIMITED
WARRANTY³**
ON AUGER GEAR CASE



VELOCITY™ THROWING SYSTEM

Quickly clears heavy snow and throws it 40% farther,¹ making snow removal easier and faster.

DUAL LED HEADLIGHTS WITH COURTESY PATH LIGHTING

Provides increased visibility by illuminating the path being cleared.

ELECTRIC CHUTE AND CONTROL POD

Easily adjusts the chute rotation and deflector angle to provide pin-point accuracy with a simple push of a button.



Signature DUAL-STAGE

Clearing snow has never been easier than with the exclusive features found in our Signature dual-stage snowthrowers. These snowthrowers give you more options than ever to tackle snow clearing jobs in a larger area. A reliable Briggs & Stratton® engine specifically designed for harsh weather gives you the power to get the job done.

24 inch clearing width
14.50 ft-lbs gross torque²

Briggs & Stratton
1450 Professional Series™
OHV Engine, 306cc
1524

28 inch clearing width
16.50 ft-lbs gross torque²

Briggs & Stratton
1650 Professional Series™
OHV Snow Engine, 420cc
1728

32 inch clearing width
21.00 ft-lbs gross torque²

Briggs & Stratton
2100 Professional Series™
OHV Snow Engine, 420cc
2132

 TEXT '**SIGNATURE**' TO 33988
TO SEE THEM IN ACTION
DATA RATES APPLY.

ADDITIONAL FEATURES: Electric start, Free Hand™ Control, durable friction disk with dual trigger steerable transmission, gear drive transmission, heated hand grips, polymer skid shoes, cast-iron gear case, 3-Year limited warranty and 1-Year commercial limited warranty.³



MEDIUM-LARGE DRIVEWAY



UP TO 60' THROWING¹
WITH VELOCITY™
THROWING SYSTEM



HEAVY SNOWFALL

Signature Pro DUAL-STAGE

There's no job too large for these models. The Signature Pro dual-stage snowthrowers have all the features a professional would demand and then some. They feature Briggs & Stratton Professional Series™ OHV engines, integrated channel handles and commercial-grade transmissions.

24 inch clearing width
16.50 ft-lbs gross torque²

Briggs & Stratton
1650 Professional Series™
OHV Snow Engine, 420cc
P1724

28 inch clearing width
21.00 ft-lbs gross torque²

Briggs & Stratton
2100 Professional Series™
OHV Snow Engine, 420cc
P2128

32 inch clearing width
21.00 ft-lbs gross torque²

Briggs & Stratton
2100 Professional Series™
OHV Snow Engine, 420cc
P2132

38 inch clearing width
21.00 ft-lbs gross torque²

Briggs & Stratton
2100 Professional Series™
OHV Snow Engine, 420cc
P2138

 TEXT '**PRO**' TO 33988
TO SEE THEM IN ACTION
DATA RATES APPLY.

ADDITIONAL FEATURES: Heated hand grips, commercial-grade Easy Turn™ friction disc drive system, cast-iron gear case, polymer skid shoes (P2138 has steel skid shoes) and 3-Year limited warranty and 1-Year commercial limited warranty.³



MEDIUM-LARGE DRIVEWAY



UP TO 60' THROWING¹
WITH VELOCITY™
THROWING SYSTEM



HEAVY SNOWFALL

¹Time, capacity and snow throwing ability can be greatly affected by conditions (model 2132 compared to model H1730E and model P2132 compared to P2132E).

²All power levels are stated gross torque at 2600 RPM per SAE J1940 as rated by Briggs & Stratton.

³See operator's manual or www.simplicitymfg.com for complete warranty details.

	SINGLE-STAGE			SINGLE-STAGE WITH SNOWSHREDDER™ AUGER		SELECT	
MODEL	1022	1022E	1022ER	1022EE	1222EE	1024	1227
AUGER/IMPELLER							
Type	Single-Stage	Single-Stage	Single-Stage	Single-Stage	Single-Stage	Dual-Stage	Dual-Stage
Clearing Width (in.)	22	22	22	22	22	24	27
Throwing Distance ¹ (ft.)	30	30	30	30	30	40	40
Intake Height (in.)	12.5	12.5	12.5	12.5	12.5	20	20
Auger Diameter (in.)	10	10	10	10	10	12	12
Auger Type	Thermal Plastic Urethane	Thermal Plastic Urethane	Thermal Plastic Urethane	SnowShredder™ Serrated Auger	SnowShredder™ Serrated Auger	Notched Steel	Notched Steel
Auger Gear Case Material	NA	NA	NA	NA	NA	Aluminum	Aluminum
Impeller Diameter (in.)	NA	NA	NA	NA	NA	12	12
No. of Impeller Blades	NA	NA	NA	NA	NA	3	3
Skid Shoes	NA	NA	NA	NA	NA	Steel Reversible	Steel Reversible
ENGINE							
Brand	Briggs & Stratton 950 Snow Series™	Briggs & Stratton 950 Snow Series™	Briggs & Stratton 950 Snow Series™	Briggs & Stratton 950 Snow Series™	Briggs & Stratton 1150 Snow Series™	Briggs & Stratton 950 Snow Series™	Briggs & Stratton 1150 Snow Series™
Technology	4-cycle, OHV	4-cycle, OHV	4-cycle, OHV	4-cycle, OHV	4-cycle, OHV	4-cycle, OHV	4-cycle, OHV
Engine Displacement (cc)	208	208	208	208	250	208	250
Gross Torque ² (ft-lbs)	9.50	9.50	9.50	9.50	11.50	9.50	11.50
Fuel Tank Capacity (qt.)	3.2	3.2	3.2	3.2	3.2	3.2	3.2
Starter	Recoil	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up
CHUTE							
Chute Material	Plastic	Plastic	Plastic	Plastic	Plastic	Steel	Steel
Chute Rotation	200° Manual	200° Manual	200° Remote Crank	200° Electric	200° Electric	200° Dash Mounted Crank	200° Dash Mounted Crank
Chute Deflector	Quick Deflector	Quick Deflector	Quick Deflector	Quick Deflector	Quick Deflector	Remote	Remote
DRIVE SYSTEM							
Drive Type	Auger-Propelled	Auger-Propelled	Auger-Propelled	Auger-Propelled	Auger-Propelled	Friction Disc Drive	Friction Disc Drive
Speeds	NA	NA	NA	NA	NA	6F - 2R	6F - 2R
Tire Size/Thread	8" x 2"	8" x 2"	8" x 2"	8" x 2"	8" x 2"	16" x 4.8"	16" x 4.8"
CONTROLS							
Free Hand™ Control	NA	NA	NA	NA	NA	Standard	Standard
Trigger Steering	NA	NA	NA	NA	NA	Standard	Standard
Heated Hand Grips	NA	NA	NA	NA	NA	Standard	Standard
OPTIONS							
Headlight	NA	NA	NA	Dual Incandescent	Dual Incandescent	Dual LED	Dual LED
Storage Cover	NA	NA	NA	NA	NA	Optional	Optional
Clean-Out Tool	NA	NA	NA	NA	NA	Standard	Standard
Drift Cutters	NA	NA	NA	NA	NA	Optional	Optional
Snow Cab	NA	NA	NA	NA	NA	Optional	Optional
Tire Chains	NA	NA	NA	NA	NA	Optional	Optional
LIMITED WARRANTY³							
Consumer	3-Years	3-Years	3-Years	3-Years	3-Years	3-Years	3-Years
Commercial	90-Days	90-Days	90-Days	90-Days	90-Days	90-Days	90-Days
Gear Case	N/A	N/A	N/A	N/A	N/A	3-Years	3-Years

¹Capacity and throwing distances can be greatly affected by conditions.

²All power levels are stated gross torque at 2600 RPM per SAE J1940 as rated by Briggs & Stratton.

³See operator's manual or www.simplicitymfg.com for complete warranty details.

SIGNATURE				SIGNATURE PRO PROFESSIONAL-DUTY			
1530	1524	1728	2132	P1724	P2128	P2132	P2138
Dual-Stage	Dual-Stage	Dual-Stage	Dual-Stage	Dual-Stage	Dual-Stage	Dual-Stage	Dual-Stage
30	24	28	32	24	28	32	38
40	55	60	60	60	60	60	60
20	23	23	23	23	23	23	23
12	14	14	14	14	14	14	14
Notched Steel	Serrated Steel	Serrated Steel	Serrated Steel	Serrated Steel	Serrated Steel	Serrated Steel	Serrated Steel
Aluminum	Cast-Iron	Cast-Iron	Cast-Iron	Cast-Iron	Cast-Iron	Cast-Iron	Cast-Iron
12	12	12	12	12	12	12	12
3	3	3	3	3	3	3	3
Steel Reversible	Polymer Reversible	Polymer Reversible	Polymer Reversible	Polymer Reversible	Polymer Reversible	Polymer Reversible	Deluxe Steel Reversible
Briggs & Stratton 1450 Professional Series™	Briggs & Stratton 1450 Professional Series™	Briggs & Stratton 1650 Professional Series™	Briggs & Stratton 2100 Professional Series™	Briggs & Stratton 1650 Professional Series™	Briggs & Stratton 2100 Professional Series™	Briggs & Stratton 2100 Professional Series™	Briggs & Stratton 2100 Professional Series™
4-cycle, OHV	4-cycle, OHV	4-Cycle, OHV	4-Cycle, OHV	4-Cycle, OHV	4-Cycle, OHV	4-Cycle, OHV	4-Cycle, OHV
306	306	420	420	420	420	420	420
14.50	14.50	16.50	21.00	16.50	21.00	21.00	21.00
3.2	3.2	3.2	5.9	3.2	5.9	5.9	5.9
Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up	Electric with Recoil Back-up
Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
200° Dash Mounted Crank	200° Electric	200° Electric	200° Electric	200° Electric	200° Electric	200° Electric	200° Electric
Remote	Electric	Electric	Electric	Electric	Electric	Electric	Electric
Friction Disc Drive	Friction Disc Drive	Friction Disc Drive	Friction Disc Drive	Commercial-Grade Friction Disc Drive	Commercial-Grade Friction Disc Drive	Commercial-Grade Friction Disc Drive	Commercial-Grade Friction Disc Drive
6F - 2R	6F - 2R	6F - 2R	6F - 2R	5F - 2R	5F - 2R	5F - 2R	5F - 2R
16" x 4.8"	16" x 4.8"	16" x 4.8"	16" x 4.8"	16" x 4.8"	16" x 4.8"	16" x 4.8"	16" x 6.5"
Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Dual LED	Dual LED	Dual LED	Dual LED	Dual LED	Dual LED	Dual LED	Dual LED
Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
3-Years	3-Years	3-Years	3-Years	3-Years	3-Years	3-Years	3-Years
90-Days	90-Days	90-Days	90-Days	1-Year	1-Year	1-Year	1-Year
3-Years	5-Years	5-Years	5-Years	5-Years	5-Years	5-Years	5-Years



THE DEALER EXPERIENCE

A neighborhood dealer who handles snowthrowers is a great resource for finding the right product. Their experience and expertise can be invaluable in ensuring you go home with the snowthrower that best meets your needs. Your Simplicity® Dealer will also provide instructions on how to operate your new snowthrower to make sure you are comfortable with the model you have selected and ready to tackle the next snowfall.



www.simplicitymfg.com



 **TEXT 'BROCHURE' TO 33988**
FOR A DIGITAL VERSION OF THIS BROCHURE
DATA RATES APPLY.



Be careful fueling your small gasoline engine in your snowthrower. Fuel with ethanol can cause damage to your engine including poor starting, rough running, rust, corrosion and in some cases failure.

Briggs & Stratton Corporation has a policy of continuous product improvement and reserves the right to modify its specifications, features or pricing without notice. Product may vary from images shown.

BRIGGS & STRATTON CORPORATION
Post Office Box 702
Milwaukee, WI 53201 USA
(414) 259-5333

Copyright ©2018. All rights reserved.
180026